

PowerNox™ B1411 Antioxidant

Introduction PowerNox[™] B1411 is a 1:1 blend of PowerNox[™] 3114 and PowerNox[™]

1680, which provides excellent protection in polyolefins.

Chemical Name Blend of PowerNox[™] 3114 and PowerNox[™] 1680 at ratio of 1:1.

CAS Number 27676-62-6 + 31570-04-4

EINECS Number 248-597-9 + 250-709-6

Chemical Structure

$$\begin{array}{c} \text{CH}_3 \\ \text{H}_3\text{C} \\ \text{H}_3\text{C} \\ \text{H}_3\text{C} \\ \text{H}_3\text{C} \\ \text{CH}_3 \\ \text{CH}_4 \\ \text{CH}_5 \\ \text{CH}_5$$

PowerNoxTM 3114, CAS No. 27676-62-6

$$\begin{array}{c} \text{CH}_3 \\ \text{H}_3 \text{C} \\ \text{H}_3 \text{C} \\ \text{H}_3 \text{C} \\ \text{CH}_3 \\ \text{CH}_3$$

PowerNoxTM 1680, CAS No. 31570-04-4



PowerNox™ B1411 Antioxidant

Chemical Formula PowerNoxTM 3114: $C_{48}H_{69} N_3O_6$

PowerNoxTM 1680: $C_{42}H_{63}O_3P$

Molecular Weight PowerNox™ 3114: 784

PowerNox[™] 1680: 647

Physical Properties

Appearance	White Power
Volatile Loss (%)	Max.0.5
Color of Solution 425nm (%)	Min.95.0
Color of Solution 500nm (%)	Min.97.0

Benefits & Applications

PowerNoxTM B1411 is instrumental in preserving the initial melt flow, reducing color creation, exhibiting robust resistance to gas fading, and ensuring sustained thermal stability.

PowerNox[™] B1411 offers long-term heat stability, protecting its physical properties in storage and use.

PowerNox[™] B1411 has the ability to resist gas fading in polyolefins and successfully counteracts the adverse discoloration effects stemming from NOX exposure.

Handling & Storage

In accordance with good industrial practice, handle with care and avoid unnecessary personal contact. Avoid continuous or repetitive breathing of dust. Use only with adequate ventilation. Protect skin. Avoid dust formation and ignition sources.

This product may be stored up to one year in a sealed container. Containers should be stored in a cool, dry area. Extended storage at elevated temperatures or exposure to direct heat or sunlight could reduce product life. Keep containers sealed when not in use.

For more detailed information please refer to the material safety data sheet.

Packing PowerNox™ B1411 is supplied in 20Kg Paper Bag, 20Kg PE Bag, 25Kg



PowerNox™ B1411 Antioxidant

Carton Box, and 50Kg Fiber Drum.

Note

All information in the leaflet is based on our present knowledge and experience. We reserve the right to make any changes according to technological progress or further developments. Performance of the product described herein should be verified by testing.

We specifically disclaim any other express or implied warranty of fitness for a particular purpose or merchantability.

We disclaim liability for any incidental or consequential damages.